

538,717

Rec'd PCT/PTO 13 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/538717

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/063487 A1

(51) International Patent Classification: E04C 5/16

(21) International Application Number:
PCT/KR2004/000012

(22) International Filing Date: 7 January 2004 (07.01.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0000955 8 January 2003 (08.01.2003) KR

(71) Applicant and

(72) Inventor: KIM, Yong Keun [KR/KR]; Hyosungsanga
Apartment 5-1405, 905 Mansu-5dong, Namdong-gu,
Incheon 405-245 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: REINFORCING BAR COUPLER



(57) Abstract: The object of this invention is to provide a reinforcing bar coupler coupling reinforcing bars in a mechanical coupling method, thus ensuring prompt and easy coupling operation and allowing the reinforcing bars to be firmly coupled to each other. The reinforcing bar coupler includes a cylindrical sleeve. The sleeve is opened at a surface thereof, and has a first seating groove on an inner surface thereof so that ends of reinforcing bars are seated therein, and a pair of first locking parts each having a first slant surface of the sleeve. A cover unit has a second seating groove on a surface thereof to cover the reinforcing bars seated in the first seating groove of the sleeve. A wedge has a pair of second locking parts each having a second slant surface, and is fitted into the sleeve to wedge the cover unit and the reinforcing bars in the sleeve.

WO 2004/063487 A1